



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

DECEMBER 2016

PRODUCT NAME

CT-LR Gum & Label Remover

PRODUCT RANGE

Part Number	Available Size
CT-LR-300	300g Aerosol
CT-LR-DP	12ml Pen
CT-LR-1L	1 Litre
CT-LR-5L	5 Litres
CT-LR-20L	20 Litres



Refer to MSDS for product safety guidelines

CT-LR Gum & Label Remover

Chemtools® Gum & Label Remover is a unique blend of citrus and hydrocarbon oils designed to dissolve adhesive gums and waxes. It allows for the quick and easy release of paper-based self-adhesive labels and stickers without rubbing or scratching. Gum & Label Remover will also dissolve some inks, as well as clean and condition rubber rollers and platens. It is harmless to most plastics, rubbers, and coatings, is ozone-safe, and does not contain halogenated solvents.

FEATURES AND BENEFITS:

- Fast and easy to use
- Allows label to be easily peeled off without rubbing or scratching
- Pleasant odour
- Harmless to most plastics, rubbers, and coatings
- Ozone safe and does not contain halogenated solvents
- Good material compatibility (always test prior to application)

COMMON USES:

- Machinery tools/implements
- Sliding door channels, slides, locks, and hinges
- Cables, couplings, gears, hitches and winches
- Hinges, electric antennas, latches, and springs
- Farming, Mining, and Marine equipment

PHYSICAL PROPERTIES:

Odour	Citrus
Density @ 20°C	0.83 g/ml
Flammability	Classified as flammable

APPLICATION METHODS:

Spray or brush generously onto the label, and allow to soak for 3 - 5 minutes, then peel off the label. Wipe away any residues that remain with a tissue or cloth. In some cases, depending upon the label, or age of the label, extra time should be allowed for the product to penetrate and soften the adhesive.

If used on plastic or varnished surfaces it is advisable to test on a small area first. Do not use on polystyrene or polycarbonate.

STORAGE:

Store in a cool, dry place, in tightly closed original containers, at a room temperature between 5°C to 40°C. Do not place in direct sunlight or near any heat source.

SAFETY:

This product contains combustible solvents. Keep away from sources of ignition. Please refer to MSDS before use. For industrial use only, please keep out of reach of children. Wear suitable safety gear before use, please refer to SDS.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.