



# A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road  
St Marys NSW 2760  
Australia

Ph: 1300 738 250 (Australia)  
Ph: +61 2 9833 9766 (International)  
Fax: 02 9623 3670

sales@chemtools.com.au  
www.chemtools.com.au

## TECHNICAL DATA SHEET

OCTOBER 2016

### PRODUCT NAME

CT-TOL Toluene

### PRODUCT RANGE

Part Number	Available Size
CT-TOL-1L	1L
CT-TOL-4L	4L
CT-TOL-20L	20L



Refer to SDS for product safety guidelines

## CT-TOL Toluene

Chemtools® Toluene is a general purpose industrial solvent that is colourless and miscible with many liquids aside from water. It has a medium evaporation rate and is an effective, economical solvent for diluting or removing paints, lacquers, oils, greases, resins, waxes, and some adhesives, from most metals via spraying, immersion, wiping, or brushing.

Toluene is commonly used in the Automotive and Manufacturing industries, and for cleaning paint tools and brushes.

#### PHYSICAL PROPERTIES:

Flash Point:	4°C
Boiling Point:	110°C
Appearance:	Clear Colourless Liquid
Odour:	Typical Aromatic
Specific Gravity @ 20°C:	0.865g/ml
Purity:	97.5%

#### APPLICATION METHODS:

Apply by spraying, dipping, wiping or brushing onto the area to be cleaned. As Toluene is a very strong solvent it may damage some plastics, elastomers and rubbers. Painted surfaces should be tested before use. Use only in a well-ventilated area well away from any sources of ignition.

#### STORAGE:

Store in a cool, dry place, in tightly closed original containers at a room temperature between 5°C and 40°C. Do not place in direct sunlight or near any heat source. Do not return any used material to its original container.

#### DISPOSAL:

All products should be disposed of in accordance with local regulations.

**PRECAUTIONS:**

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the material.

**WARRANTY:**

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the product's suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.