



Technical Data Sheet

ChemTools **ESD Floor Treatment & Maintenance**

Description:

ChemTools Floor Treatment & Maintenance is designed to be safe on all floor surfaces, being a neutral floor cleaner, specially formulated to keep gloss floors shiny. It is a fast acting product, and will not leave sticky residues, nor require rinsing. It can be used with most floor coatings and gives excellent results.

Function:

ChemTools Anti Static Floor Neutraliser is part of the ChemTools Anti Static Floor Care System consisting of (in sequence of application):

- ChemTools Anti Static Floor Stripper
- ChemTools Anti Static Floor Neutraliser & Cleaner
- ChemTools Anti Static Floor Coating
- ChemTools Anti Static Floor Treatment & Maintenance

ChemTools Anti Static Floor Treatment & Maintenance chemistry has been formulated to work in conjunction with ChemTools Floor Stripper, Neutraliser and Anti-static Coating. It is a full fragrance, high performance cleaner formulated for both delicate floor surfaces, like marble, terrazzo, slate and timber floors, yet with the power punch detergency to remove heavy grime build-up and sludge found in factories and retail centres. It is a non acidic and non alkaline formula so ChemTools Floor Treatment & Maintenance won't blush, burn or bite at gloss or haze the thinnest of floor sealer coats. Without the greasy residue found with normal detergent you'll find it a great performer on ceramic and quarry tile - and it won't leave a slippery residue.

Features:

- Delicate yet effective on factory floor surfaces.
- Non acidic and non alkaline formula.
- Will not burn or haze gloss surfaces
- Can be applied via mop or automatic equipment.
- Non slip finish.
- Has a fresh citrus aroma without being cloying harsh fragrance.
- Contains no ammonia, silicates or solvents that would degrade floor sealers – therefore will provide longer life for your floors.
- Developed for high Traffic ESD areas.

Application:

Normal day to day Maintenance of floor

Use ChemTools Anti Static Floor Treatment & Maintenance product to maintain the high gloss and performance of your ESD Coating.



Technical Data Sheet

Directions- No Need for Hot Water

- *Damp Mopping*

Add approximately 100ml (approx 1/3 cup) per wringer bucket of cold water. If mopping prior to a recoat, use the double bucket technique or use a second person to rinse up heavy soiling if present. This helps prevent bounce in soil and extends stripping cycles.

- *Heavy Soilage*

On extra soil add up to half a cup of ChemTools Floor Treatment & Maintenance per wringer bucket of cold water. Auto-scrubbing ChemTools Floor Treatment & Maintenance is a low foaming product, and is ideally suited for auto scrubbing in factories, laboratories, shopping centres and supermarkets.

Mix 500ml per 50L (1:100) cold water, for normal soilage. Use soft pads for delicate surfaces like granite, marble or terrazzo (white, tan or pale blue). Use red, blue or green pads or brushes that require a deep cleaning or scrubbing.

- *Cutting Back*

ChemTools Floor Treatment & Maintenance is ideal for light cutting back of floor finishers. Dilute 1 part 'Treatment & Maintenance' to 20 parts water, leave on for a few minutes and scrub with a blue or green pad and rinse prior to recoating.

Safety:

- If product enters eyes – flush with copious amounts of water for at least 10 minutes - if problem still persists, seek medical assistance.
- If the material comes into contact with the skin, the affected area should be washed with soap and water.
- Spillage of the material should be mopped up with sand or sawdust.
- Dispose of waste material in accordance to local or national regulations.
- Dispose of empty can in recycle facilities.
- Clean equipment in accordance to equipment manufacturers instructions
- Wash Hands with soap and water after use.

Storage:

Store in a cool, dry place, out of the reach of children, in original containers, at a room temperature between 5°C to 30°C. Please do not return any used material to its original container.

Disposal:

All products should be disposed of in accordance with local regulations.

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the material.

Warranty: All products purchased from or supplied by ChemTools are subject to terms and conditions set out in the contract. ChemTools warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by ChemTools is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. ChemTools makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.