

2023 - 2024
CATALOGUE



GREASES & ANTI-SEIZES

WWW.CHEMTOOLS.COM.AU



CONTENTS

PRODUCTS

ANTI-SEIZE LUBRICANTS

DEOX R06 Graphite Anti-Seize
 DEOX R10 Rust Breaking Penetrating Oil
 DEOX R23 Food Safe Anti-Seize
 DEOX R28 Nickel Anti-Seize
 DEOX R29 Copper Anti-Seize
 DEOX R47 Silver Grade Anti-Seize
 DEOX R75 Pure Zinc Anti-Seize (Aircraft Grade)
 DEOX R81 Marine Grade Anti-Seize

Premium Anti-Seize 6
 Bolt Penetrant 7
 Specialty Anti-Seize 7
 Premium Anti-Seize 6
 Premium Anti-Seize 6
 Premium Anti-Seize 6
 Specialty Anti-Seize 7
 Specialty Anti-Seize 7

BENTONITE-BASED GREASE

DEOX R45 High Temperature Non-Melt Grease

Bulk Greases

8

CLEANING PRODUCTS

Delicate Task Wipes
 Kleanitize Citra-Grit Hand Cleaner
 Kleanitize Mint-Grit Hand Cleaner
 Lint Free Wipes

Static Free Wipes 5
 Hand Cleaners 9
 Hand Cleaners 9
 Static Free Wipes 5

DIELECTRIC GREASE

Thermalle™ BULB & CONNECTOR Dielectric Grease
 Thermalle™ TEF-EASE Dielectric Dissimilar Metals Anti-Corrosion & Anti-Seizing Gel
 Thermalle™ VOLTGUARD Electrician's Dielectric Grease

Specialty Greases 3
 Specialty Greases 4
 Specialty Greases 3

ELECTRICALLY CONDUCTIVE GREASE

Thermalle™ CARBOVOLT Carbon Conductive Grease
 Thermalle™ CONDUSIL Silver Electrically Conductive Grease
 Thermalle™ ELECTRASEAL-COPPER Electrical Jointing Compound
 Thermalle™ ELECTRASEAL-NICKEL Electrical Jointing Compound
 Thermalle™ ELECTRASEAL-ZINC Electrical Jointing Compound

Specialty Greases 4
 Specialty Greases 4
 Specialty Greases 4
 Specialty Greases 4
 Specialty Greases 4

FOOD SAFE GREASE

DEOX R20 Food Safe Machine Grease
 DEOX R35 White Petroleum Jelly

Bulk Greases 9
 Bulk Greases 9

LANOLIN-BASED GREASE

DEOX R555 All Purpose Lanolin Wool Grease

Bulk Greases

8

LITHIUM-BASED GREASE

DEOX R03 White Lithium Grease
 DEOX R41 High Grade Blue Lithium Complex Grease
 DEOX R42 Premium Heavy Duty Molytack Grease
 DEOX R43 Premium EP Red Lithium Complex Grease
 DEOX R999 High Grade Truck & Farm Grease
 Thermalle™ TEF-GLIDE Electrical & Automotive White Lithium Grease

Bulk Greases 8
 Bulk Greases 8
 Bulk Greases 8
 Bulk Greases 8
 Bulk Greases 9
 Specialty Greases 3

MARINE SPECIALISED GREASE

DEOX R888 Premium Heavy Duty Marine Grease
 Thermalle™ TEF-EASE Dielectric Dissimilar Metals Anti-Corrosion & Anti-Seizing Gel

Bulk Greases 9
 Specialty Greases 4

THERMALLY CONDUCTIVE GREASE

Thermalle™ CERAMIC Silicone-Free Thermally Conductive Grease
 Thermalle™ SILVER-FROST Silver Thermally Conductive Grease
 Thermalle™ SUB-ZERO Thermally Conductive Grease

Specialty Greases 3
 Specialty Greases 3
 Specialty Greases 3

VACUUM & OXYGEN SAFE GREASE

Thermalle™ OXYGUARD Oxygen Safe Grease with PFPE
 Thermalle™ VACUSEAL Silicone-Free High Vacuum Grease
 Thermalle™ VACUSEAL-PLUS Silicone High Vacuum Grease

Specialty Greases 5
 Specialty Greases 5
 Specialty Greases 5

SPECIALTY GREASES

THERMALLE™ CERAMIC

Silicone-Free Thermally Conductive Grease

Non-reactive, non-flowing ceramic-filled compound. Non-electrical, high thermal conductivity. Low thermal resistance. Low creep and low bleed.

Increases heat transfer by over 50%. Stable over a wide temperature range.

For high powered CPU's, heavy heatsinks, and other demanding cooling applications.

Low toxicity.



PART NO.	SIZE
CT-TM000-2ML-BL3	2ml Tube (Pack of 3)
CT-TM000-05PT	5ml Syringe
CT-TM000-10PT	10ml Syringe
CT-TM000-50T	50g Tube
CT-TM000-250G	250g/6oz Cartridge
CT-TM000-1KG	1 Kilogram

THERMALLE™ SILVER-FROST

Silver Thermally Conductive Grease

Exceptional thermal interfacing.

Occupies and seals voids. Amplifies conductivity across uneven mating surfaces.

Highly reliable, and stable. High concentration of silver particles and other proprietary fillers.

Dissipates heat efficiently. Prevents current leakage.

Non-flowing with low bleed.



PART NO.	SIZE
CT-TM002-2ML-BL3	2ml Tube (Pack of 3)
CT-TM002-05PT	5ml Syringe
CT-TM002-10PT	10ml Syringe
CT-TM002-50T	50g Tube
CT-TM002-250G	250g/6oz Cartridge
CT-TM002-1KG	1 Kilogram

THERMALLE™ TEF-GLIDE

Electrical & Automotive White Lithium Grease

Lithium-based grease. Enhanced lubricity with PTFE. Superior wear protection.

Resists water and protects from corrosion.

High drop point. Remains smooth and buttery under a wide operating temperature range.

Suitable for garden and farming machinery. Can be used on marine equipment under most environmental conditions.

Commonly used by auto-mechanics.

Non-toxic and environmentally safe.



PART NO.	SIZE
CT-TM004-05PT	5ml Syringe
CT-TM004-10PT	10ml Syringe
CT-TM004-50T	50g Tube
CT-TM004-250G	250g Tub
CT-TM004-1KG	1 Kilogram

THERMALLE™ SUB-ZERO

Silicone Thermally Conductive Grease

Non-corrosive. High performance. Long lasting.

Non-flowing thermal interface. Low bleed. Excellent conductivity and stability.

Wide temperature range. Suits all heat generating devices.

Commonly used for computer processors, graphics cards, power supplies, and lighting systems.

Found in the automotive industry for engine control units, power steering systems, and transmission control modules.



PART NO.	SIZE
CT-TM001-05PT	5ml Syringe
CT-TM001-10PT	10ml Syringe
CT-TM001-50T	50g Tube
CT-TM001-250G	250g/6oz Cartridge
CT-TM001-1KG	1 Kilogram

THERMALLE™ VOLTGUARD

Electrician's Dielectric Grease

Premium, non-toxic silicone-based grease.

Superior electrical insulation.

Excellent lubrication and water resistance. High corrosion protection.

Non-curing and non-melting.

Withstands extreme temperatures and harsh environments.

Commonly applied to spark plug boots, battery terminals, automotive ignition systems, and electrical switches.

Compatible with most plastics and rubbers. Suitable for o-rings and seals.



PART NO.	SIZE
CT-TM003-05PT	5ml Syringe
CT-TM003-10PT	10ml Syringe
CT-TM003-50T	50g Tube
CT-TM003-250G	250g Tub
CT-TM003-1KG	1 Kilogram

Thermalle™ VOLTGUARD is also available in a pack of three 2ml single-use tubes as a:

Bulb & Connector Dielectric Grease

PART NO.	SIZE
CT-TM003-2ML-BL3	2ml Tube (Pack of 3)

Thermalle™ BULB & CONNECTOR Dielectric Grease is a premium, non-toxic silicone-based grease that seals and protects to prevent shorts, and lubricates to allow easier installation and removal of bulbs.

Bulb & Connector Grease provides superior insulation, excellent water and heat resistance, and high corrosion protection for both indoor and outdoor applications.

Other recommended uses include battery terminals, automotive ignition systems, headlights, and tail lights, and a variety of other electrical connections.



SPECIALTY GREASES

THERMALLE™ TEF-EASE

Dielectric Dissimilar Metals Anti-Corrosion & Anti-Seizing Gel

Pure synthetic grease. No silica, petroleum additives, or volatile solvents. Contains PTFE for high lubricity.

Prevents corrosion and resists seizing and galling. Excellent electrical insulation and protection. High dielectric properties. Long lasting adhesion.

Non-curing and non-melting.

Completely waterproof and resists wash-out in both salt and fresh water.

Prevents metal-to-metal contact.

PART NO.	SIZE
CT-TM005-05PT	5ml Syringe
CT-TM005-10PT	10ml Syringe
CT-TM005-50T	50g Tube
CT-TM005-250G	250g Tub
CT-TM005-1KG	1 Kilogram

Thermalle™ TEF-EASE performs perfectly when under extreme pressures and high loads.



THERMALLE™ CONDUSIL

Silver Electrically Conductive Grease

Formulated with pure silver-based additives. Contains no graphite or mercury. High lubricity.

Excellent electrical conductivity and high performance.

Reduces resistance and eliminates hot spots caused by poor contact.

Protects against moisture intrusion. Resists corrosion build-up across a wide operating temperature range.

Ideal for preventing data errors and power interruptions in ignition systems and other electrical connections.

PART NO.	SIZE
CT-TM006-05PT	5ml Syringe
CT-TM006-10PT	10ml Syringe
CT-TM006-50T	50g Tube
CT-TM006-250G	250g/6oz Cartridge

Thermalle™ CONDUSIL is suitable for use with metals, plastics, and rubbers.



THERMALLE™ CARBOVOLT

Carbon Conductive Grease

Contains a proprietary carbon filler. Suits irregular surfaces and loose or vibrating parts.

Improves the connection between worn contacts and non-moving mating surfaces. Reduces arcing hot spots.

Excellent conductivity and lubrication.

Resists water washout. Prevents the formation of oxides, sulphides, and other corroding deposits.

PART NO.	SIZE
CT-TM007-05PT	5ml Syringe
CT-TM007-10PT	10ml Syringe
CT-TM007-50T	50g Tube
CT-TM007-250G	250g Tub
CT-TM007-1KG	1 Kilogram
CT-TM007-2.5KG	2.5 Kilograms

Thermalle™ CARBOVOLT will not cure or melt. It performs well with low bleed and low evaporation.



THERMALLE™ ELECTRASEAL-NICKEL

Electrical Jointing Compound

For use on aluminium-to-aluminium and aluminium-to-copper pad-to-pad or palm-to-palm joints.

Non-setting, non-flowing, and non-drying paste.

Contains a mineral oil base with highly conductive materials.

Ensures low resistance electrical connections continue with excellent conductivity.

Remains pliable, even at low temperatures, allowing for easy joint disassembly and reassembly.

PART NO.	SIZE
CT-TM008-50T	50g Tube
CT-TM008-250G	250g Tub
CT-TM008-1KG	1 Kilogram
CT-TM008-2.5KG	2.5 Kilograms

Water resistant. Stops corrosion from forming when in the presence of moisture caused by environmental factors.



THERMALLE™ ELECTRASEAL-COPPER

Electrical Jointing Compound

For improving electrical connections between copper conductors.

Non-setting, non-flowing compound. Contains a solvent-refined mineral oil base.

Provides excellent, reliable, and long-lasting electrical conductivity.

Protects from corrosion and oxidation.

Ideal for power distribution systems, underground cabling, electrical equipment and components, and telecommunication systems.

Non-flammable and non-toxic.

Provides high resistance to dust, water, and moisture. Will not dry and remains pliable.

PART NO.	SIZE
CT-TM009-50T	50g Tube
CT-TM009-250G	250g Tub
CT-TM009-1KG	1 Kilogram
CT-TM009-2.5KG	2.5 Kilograms



THERMALLE™ ELECTRASEAL-ZINC

Electrical Jointing Compound

For use on aluminium-to-aluminium and aluminium-to-copper bolted and compression settings.

Non-setting, non-flowing, and non-drying paste.

Contains a mineral oil base with highly conductive materials.

Ensures low resistance electrical connections continue with excellent conductivity.

Remains pliable, even at low temperatures, allowing for easy joint disassembly and reassembly.

PART NO.	SIZE
CT-TM010-50T	50g Tube
CT-TM010-250G	250g Tub
CT-TM010-1KG	1 Kilogram
CT-TM010-2.5KG	2.5 Kilograms

Water resistant. Stops corrosion from forming when in the presence of moisture caused by environmental factors.



SPECIALTY GREASES

THERMALLE™ VACUSEAL

Silicone-Free High Vacuum Grease

High quality non-toxic lubricant specially formulated for use in vacuum systems.

Provides needed lubrication and sealing of o-rings, gaskets, and valves.

Free of halogens and heavy metals.

Compatible with most metal, plastic, and elastomer system components.

Good general purpose hydrocarbon grease.

Contains microparticles of PTFE.

Resistant to oxidation and thermal degradation at temperatures below 30°C.

Ensures smooth sliding and rolling of bearings in pumps and compressors.

Note:
NOT advised
for products
that may
warm to or
exceed 30°C.
For temps up
to 260°C, use
VACUSEAL PLUS



PART NO.	SIZE
CT-TM011-50T	50g Tube
CT-TM011-250G	250g Tub

THERMALLE™ VACUSEAL-PLUS

Silicone High Vacuum Grease

For use in pressure and vacuum units up to 10⁻⁶ millibars and up to 260°C.

Reduces leakage by filling gaps and lowering permeation rates.

Silicone base ensures resistance to oxidation and thermal degradation.

Contains no additives that react negatively with system components.

Offers high lubricity for sliding and rolling bearings and gears.

Protects from water ingress, corrosion formation, and most chemical intrusions.

Performs well as an anti-seize for glass components.

Thermalle™
VACUSEAL-
PLUS safely
seals and
lubricates
all metals,
plastics, and
elastomers
at high temps.



PART NO.	SIZE
CT-TM012-50T	50g Tube
CT-TM012-250G	250g Tub

THERMALLE™ OXYGUARD

Non-Flammable Oxygen Safe Grease with PFPE

Contains a medium viscosity perfluorinated polyether (PFPE) base oil thickened with PTFE.

Physically and chemically inert and safe for high pressure air, nitrous oxide, and oxygen systems with no fear of combustion.

Compatible with the most aggressive chemical and gas applications. Completely resistant to water and all common chemicals. Resistant to oxidation and thermal degradation.

Exceptional thermal stability. Formulated for lifetime sealed maintenance bearings, extreme long-term lubrication, and resistance to friction and component wear.

Safe for use in breathing regulators for scuba diving, personal protective equipment, and medical purposes.

✓ **OXYGUARD**
is **FREE** from
petroleum-based
ingredients



PART NO.	SIZE
CT-TM013-05PT	5ml Syringe
CT-TM013-10PT	10ml Syringe
CT-TM013-50T	50g Tube
CT-TM013-250G	250g Tub



COMMON APPLICATIONS

- Bearings, stop cocks, o-rings, and gaskets in wet or dry conditions
- All types of bearing threads in aggressive or corrosive conditions, incl. temperature extremes
- Lifetime sealed, maintenance-free bearings
- Mechanical parts operating at high vacuum conditions in contact with aggressive chemicals or oxygen
- Components operating under medium load at high speed
- Breathing regulators for scuba diving, personal protective equipment, and medical purposes
- Articulation components subjected to consistent high temperatures
- Clean room applications in the food, nuclear, chemical, oxygen, and aerospace industries

STATIC FREE WIPES

LINT FREE WIPES

High strength, highly absorbant, and completely sterile. Static-free when used with liquids - dust will not cling.

Non-scratch and extremely soft. Ideal for sensitive parts and equipment.

Compatible with many liquids and solvents.

Pack contains 100 wipes.



PART NO.	SHEET SIZE	MATERIAL
CT-LFW-100	30cm x 35cm	Non-woven blend of polyester and lyocell

DELICATE TASK WIPES

Light duty 280 pack, 1-ply wipes. High strength when wet or dry.

Static neutral when used with liquids - dust will not cling.

Ultra low linting and scratch-free.

Ideal for sensitive parts and equipment. Compatible with many liquids and solvents.



PART NO.	SHEET SIZE	MATERIAL
CT-LFW-280-30	20cm x 11cm	Recycled and virgin wood fibres

PREMIUM ANTI-SEIZE

Chemtools® premium range of DEOX anti-seize lubricants protect parts and equipment against seizing under extreme temperatures, allowing for easy disassembly. Each customer approved specialty formulation offers excellent resistance to chemicals, salt water, and exposure to the elements, and will minimise corrosion on threaded parts.

All products in the DEOX range share the same quality-tested attributes, including:

- Non-hardening and non-dripping
- High resistance to galling
- Remains homogenous during storage

DEOX R06 GRAPHITE ANTI-SEIZE



Contains pure graphite.

For use on corrosion resistant alloys, austenitic stainless steel, nickel, titanium, and cobalt.

Meets Military Specification: MIL-PRF-907F

PART NO.	SIZE
CT-R06-75T	75g Tube
CT-R06-500BT	500g Brush Top
CT-R06-2.5KG	2.5 Kilograms

DEOX R29 COPPER ANTI-SEIZE



For use on alloys, plastics, steel, brass, and copper. Not suitable for stainless steel.

Meets Military Specification: MIL-PRF-907F

PART NO.	SIZE
CT-R29-35BT-POS	35g Brush Top Point of Sale (POS) Box (Contains 25pcs)
CT-R29-75T	75g Tube
CT-R29-300	300g Aerosol
CT-R29-500BT	500g Brush Top
CT-R29-2.5KG	2.5 Kilograms

DEOX R28 NICKEL ANTI-SEIZE



For use on stainless steel and metals where the presence of copper is restricted. Recommended for austenitic stainless steel, nickel, titanium, cobalt, and other alloys.

PART NO.	SIZE
CT-R28-35BT-POS	35g Brush Top Point of Sale (POS) Box (Contains 25pcs)
CT-R28-75T	75g Tube
CT-R28-300	300g Aerosol
CT-R28-500BT	500g Brush Top
CT-R28-2.5KG	2.5 Kilograms

DEOX R47 SILVER GRADE ANTI-SEIZE



For most metals including soft metals and where dissimilar metals are used. Recommended for aluminium and its alloys where the presence of copper is restricted.

PART NO.	SIZE
CT-R47-75T	75g Tube
CT-R47-500BT	500g Brush Top
CT-R47-2.5KG	2.5 Kilograms

SPECIALTY ANTI-SEIZE

DEOX R75 PURE ZINC ANTI-SEIZE (AIRCRAFT GRADE)



TEMPERATURE RANGE
 -155°C +399°C

Advanced anti-corrosion lubricating paste for iron, aluminium, and aluminium alloys. Suitable for use between dissimilar metals. Compatible with plastics. Contains extra-fine pure zinc particles within a petrolatum compound. Application activates electrochemical galvanising properties to halt corrosion. Water resistant and formulated to lower friction, reduce wrench torque, and prevent extreme temperature seizing.

Increases assembly and disassembly speeds on threaded components - even after lengthy service or severe conditions.

Commonly found in the farming and mining industries where the reuse of non-corroded, non-seized metal joints and pipes is required.

Ensures lubrication of drills, taps, studs, bolts, nuts, hinges, valve fixtures, chains, gears, flanges, pump fittings, keyways, and more.

PART NO.	SIZE
CT-R75-75T	75g Tube
CT-R75-500BT	500g Brush Top
CT-R75-2.5KG	2.5 Kilograms

Non-hardening. Remains homogenous during storage.

Meets Military Specification:
CID A-A-59313 (form. MIL-T-22361).

DEOX R23 FOOD SAFE ANTI-SEIZE



TEMPERATURE RANGE
 -50°C +400°C

Safe for use in the Beverage, Food, Cosmetics, and Pharmaceutical industries.

Extremely high performance on all metals, especially stainless steel.

Fortified with PTFE for maximum lubrication. Contains anti-corrosion additives. Will not harden or drip.

Prevents galling and high temperature seizing on threaded joints and metal parts. Remains undetectably odourless and tasteless.

PART NO.	SIZE
CT-R23FS-75T	75g Tube
CT-R23FS-300	300g Aerosol
CT-R23FS-500BT	500g Brush Top
CT-R23FS-2.5KG	2.5 Kilograms

Protects against acids and water-based cleaning products. Resistant to most chemicals, salt water, and exposure to the elements. Formulated under strict conditions.

DEOX R81 MARINE GRADE ANTI-SEIZE



TEMPERATURE RANGE
 -50°C +318°C

Advanced non-metallic compound for all metal types.

Protects assemblies in wet, humid conditions. Resists washout. High resistance to saltwater corrosion in harsh marine and offshore environments. Insulates to inhibit galvanic corrosion between dissimilar metals.

Non-curing, no-drip barrier.

Reduces friction under extreme pressure and high temperatures. High performing with excellent lubricity.

Increases assembly and disassembly speeds on threaded components.

Provides ongoing rust protection on sensitive or galling-prone alloys such as chrome and inconel.

Marine applications commonly include: anchor pullies, rigging and hoist cables, winches, pump gaskets and flanges, engine and housing fasteners, hatch cover hinges, and assembly parts such as bushings, nuts, bolts, studs, and screws.

PART NO.	SIZE
CT-R81-75T	75g Tube
CT-R81-500BT	500g Brush Top
CT-R81-2.5KG	2.5 Kilograms

BOLT PENETRANT

DEOX R10 RUST BREAKING PENETRATING OIL



Premium blend of refined low viscosity mineral oils for the maintenance and servicing of machinery and equipment. Lubricates to increase performance in a matter of minutes.

Swiftly flows into narrow spaces.

Dissolves sludge and grime.

Breaks rust to unseize moving parts.

Contains corrosion inhibitors.

PART NO.	SIZE
CT-R10-300	300g Aerosol
CT-R10-5L	5 Litres
CT-R10-20L	20 Litres

BULK GREASES

DEOX R03 WHITE LITHIUM GREASE

Premium, all-purpose lubricating grease. Contains PTFE for superior performance and protection.

Excellent water resistant barrier. Prevents rust and corrosion build-up. Reduces friction and wear.

Forms a long lasting protective film. Will not harden, melt, drip, migrate, or wash away. Low bleed and low evaporation.

Improves electrical connections between worn contacts. Reduces arcing hot spots and pitting on switch contact surfaces.

Ensures silent operation between metal to metal moving parts under stress.

PART NO.	SIZE
CT-R03-50G	50g Tube
CT-R03-350	350g Aerosol
CT-R03-450G	450g Cartridge
CT-R03-2.5KG	2.5 Kilograms



DEOX R41 HIGH GRADE BLUE LITHIUM COMPLEX GREASE

Premium general purpose tacky grease.

Continuous high performance.

Excellent mechanical stability, oxidation resistance, and anti-wear characteristics.

Resistant to heat, moisture, and most chemicals

Formulated for use under tough, wet, and hot conditions and environments.

Excellent water & moisture barrier. Long lasting rust and corrosion protection.

Extends the service life of machinery, equipment, and moving parts.

Increases the life of chains, wire ropes, cables, disc brakes, wheel bearings, and gears.

PART NO.	SIZE
CT-R41-450G	450g Cartridge
CT-R41-2.5KG	2.5 Kilograms



DEOX R42 PREMIUM HEAVY DUTY MOLYTACK GREASE

Lithium complex thickened. Fortified with molybdenum disulphide. Better adhesion with functional polymers. Protects from friction and wear.

Exceptional load carrying capacity.

Blended with special fluids for high film strength and advanced performance.

Resists extreme temperature and pressure conditions. High dropping point.

Long lasting rust and corrosion protection.

Suits metals and moving parts in the presence of water.

Increases the life of chains, wire ropes, cables, disc brakes, wheel bearings and gears.

Extends the service life of machinery and parts.

PART NO.	SIZE
CT-R42-450G	450g Cartridge
CT-R42-2.5KG	2.5 Kilograms



DEOX R43 PREMIUM EP RED LITHIUM COMPLEX GREASE

High grade lubricating qualities.

Excellent long lasting no-drip barrier.

Fantastic corrosion and anti-wear properties.

Suits a wide range of extreme pressure environments

Exhibits high lubricity in operating temperatures between 5°C and 250°C.

Contains polymers, tackifiers and base oils to ensure adhesion - even in less desirable conditions.

Formulated for harsh outdoor climates.

Extends the service life of machinery and equipment used in construction, roadwork, farming, automotive, mining, and marine.

PART NO.	SIZE
CT-R43-450G	450g Cartridge
CT-R43-2.5KG	2.5 Kilograms



DEOX R45 HIGH TEMPERATURE NON-MELT GREASE

Advanced, wide temperature bentonite-based formula.

Contains no complex soap thickeners.

Long lasting corrosion and anti-wear protection.

Extends the service life of machinery and equipment operating at high temperatures.

Non-melting with no dropping point. Resists softening and remains in place.

Resists water wash-out.

Provides excellent mechanical stability.

Highly recommended for anti-friction bearings.

Can be used on overhead conveyor bearings at maximum temperatures. Ideal for spindles and disc brakes.

PART NO.	SIZE
CT-R45-450G	450g Cartridge
CT-R45-2.5KG	2.5 Kilograms



DEOX R555 ALL PURPOSE LANOLIN WOOL GREASE

Superior long term corrosion preventative. Thick and tacky. Protects from humidity, moisture, mild chemical assaults, acids, and salt spray deposits.

Excellent dielectric grease. Non-conductive up to 70kV. Reduces wear and stops seizing. Resists oxidation. Protects electrical connections and battery terminals.

Non-toxic and safe for aquatic and plant life. Resists wash-out. Naturally free of solvents and chemicals.

Compatible with metals, plastics, and painted surfaces. Great preventative film for long term storage.

Protects machinery blades, nuts and bolts, gears and levers, locks, hinges, and runners.

Safe for use in hydraulic & pneumatic tools.

PART NO.	SIZE
CT-R555-450G	450g Cartridge
CT-R555-2.5KG	2.5 Kilograms
CT-R555-19KG	19 Kilograms



BULK GREASES

DEOX R888 PREMIUM HEAVY DUTY MARINE GREASE

Calcium sulphonate base. Forms a protective fish scale-like coating.

Excellent long term corrosion protection and extreme pressure properties. Superior lubrication in wet or moisture-saturated environments. Reduces wear and friction.

Remains resistant to oxidation and high temperatures. Ideal for use where exposure to harsh elements occurs consistently.

Neutralises strong acids and disperses harmful deposits, including salt spray.

Recommended for winches, hinges, pins, trailers, outboard assemblies, ball, roller and wheel bearings, pumps, and axles.



PART NO.	SIZE
CT-R888-450G	450g Cartridge
CT-R888-2.5KG	2.5 Kilograms

DEOX R999 HIGH GRADE TRUCK & FARM GREASE

Maximum performance grease. Lithium complex thickened. Formulated for heavy duty fleet, agricultural, and automotive applications.

Long lasting protection. Superior anti-wear performance. High drop point.

Withstands extreme temperature and pressure conditions. Provides superior lubrication and rust inhibition for metal and moving parts.

Can be used in the presence of water. Functional polymers ensure adhesion in wet environments and extreme weather.

Recommended for bearings, pins and bushes, couplings, and turntables.



PART NO.	SIZE
CT-R999-450G	450g Cartridge
CT-R999-2.5KG	2.5 Kilograms

DEOX R20 FOOD SAFE MACHINE GREASE

Contains pharmaceutical base oils and a complex calcium sulphonate thickener. Safe for use in areas of incidental food contact. Universally compatible with industrial kitchen appliances.

High performing lubrication for mildly acidic and very wet environments. Excellent thermal stability. High drop point.

Exceptional mechanical stability and extreme pressure resistance with very high load carrying capacity.

Superior waterproof properties and high resistance to wash-out. Excellent resistance to oxidation and corrosion.

Protects from wear and friction. Reduces scuffing, scoring, and seizure of contacting surfaces.



PART NO.	SIZE
CT-R20FS-50G	50g Tube
CT-R20FS-300	300g Aerosol
CT-R20FS-450G	450g Cartridge
CT-R20FS-2.5KG	2.5 Kilograms



DEOX R35 WHITE PETROLEUM JELLY

Highly viscous, stable assembly lubricant. Non-toxic, non-staining, and odourless. Contains an ash-free mixture of highly refined mineral oils and purified hydrocarbons.

Smooth, grease-like texture. Good oil retaining capacity - even at elevated temperatures.

Ideal for temporary corrosion protection. Insoluble with water and easily removable with solvents.

Certified for use as a surface lubricant in the manufacture of metallic articles. Safe for use in pharmaceutical, cosmetic, and food processing industries.



PART NO.	SIZE
CT-R35-1KG	1 Kilogram
CT-R35-2.5KG	2.5 Kilograms
CT-R35-18KG	18 Kilograms

HAND CLEANERS

KLEANITIZE CITRA-GRIT & MINT-GRIT HAND CLEANERS

Premium, solvent-free industrial strength heavy duty hand wash. Removes the toughest soils, including grease. Contains ultra-fine exfoliating particles to soften hard working hands.

Active chelating ingredient binds with common heavy metals, allowing them to be washed away with water.

Neutralises strong workshop odours.

Kills a broad array of bacterial germs.

Does not sting or burn cuts, scrapes, and open wounds. Will not scratch or irritate sensitive skin.

Leaves skin feeling smooth and smelling pleasant.

Highly recommended for all workshops and manufacturing facilities.



PART NO.	SIZE
CT-HC-500ML	500ml Finger Pump
CT-HC-5L	5 Litre Hand Pump
CT-HC-20L	20 Litre Drum

PART NO.	SIZE
CT-MHC-500ML	500ml Finger Pump
CT-MHC-5L	5 Litre Hand Pump
CT-MHC-20L	20 Litre Drum

NOTES



NOTES



GREASES & ANTI-SEIZES

**2023 - 2024
CATALOGUE**



AUSTRALIA PH: 1300 738 250

NEW ZEALAND PH: +64 3 323 4177 • SINGAPORE PH: +65 6 363 2643

YOUR LOCAL SALES REPRESENTATIVE IS:

**AUSTRALIAN MANUFACTURING FACILITY:
UNIT 2, 14 - 16 LEE HOLM ROAD ST MARYS NSW 2760 AUSTRALIA**

V2-2024.02.07

CHEMTOOLS.COM.AU • CHEMTOOLS.CO.NZ