



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

ISSUED OCTOBER 2020 (VALID 5 YEARS FROM THE DATE OF ISSUE)

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

SUPPLIER	CHEMTOOLS PTY LTD	PHONE	1300 738 250 (Business Hours)
ADDRESS	Unit 2, 14 – 16 Lee Holm Road ST MARYS NSW 2760	FAX	02 9623 3670
		WEBSITE	www.chemtools.com.au

PRODUCT NAME	GalMax™ ETCH Black Etch Primer		
PART NUMBER	CT-EPBK	PRODUCT TYPE	Primer
PRODUCT USE	Primer for ferrous and non-ferrous metals		
CREATION DATE	September 2020	LATEST REVISION DATE	Refer to date of issue above

SECTION 2: HAZARDS IDENTIFICATION

Statement of Hazardous Nature	Classified as HAZARDOUS according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS).
SUSMP Classification	Schedule 5
ADG Classification	Classified as DANGEROUS GOODS by the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail and the New Zealand NZS5433: Transport of Dangerous Goods on Land
UN Number	1263, PAINTS LFP (MEK, ISOPROPANOL)
Hazchem Code	3YE
Packing Group	II
GHS Signal Word	DANGER
GHS Hazard Pictograms	

HAZARDOUS CLASSIFICATIONS

Flammable Liquids	Category 2
Aspiration Hazard	Category 1A
Acute Toxicity Oral	Category 3
Acute Toxicity Inhalation	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Irritation	Category 2A
Specific Target Organ Toxicity (Single Exposure)	Category 3 Narcotic Effects

HAZARD STATEMENTS

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 2 of 2

This revision issued October 2020

H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H319	Causes serious eye irritation.
H315	Causes skin irritation.

PREVENTION PRECAUTIONARY STATEMENTS

P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fumes, gas, mist, vapours, or spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective clothing, gloves, eye/face protection and suitable respirator.

RESPONSE PRECAUTIONARY STATEMENTS

P101	If medical advice is needed, have product container or label at hand.
P301+P310	IF SWALLOWED: immediately call a POISONS CENTRE or doctor.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P312	Call a POISONS CENTRE or doctor if you feel unwell.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists, get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.

STORAGE PRECAUTIONARY STATEMENTS

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 3 of 3

This revision issued October 2020

DISPOSAL PRECAUTIONARY STATEMENTS

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Chemical Entity	CAS Number	Proportion
Methyl Ethyl Ketone	78-93-3	> 30%
Isopropyl alcohol	67-63-0	< 30%
Bisphenol A-Bisphenol A didlycidyl ether polymer	25036-25-3	< 15%
1 methoxy-acetate-2-Propanol; PM Acetate	108-65-6	< 15%
Xylene	1330-20-7	< 15%
Ethyl Benzene	100-41-4	< 5%
Other ingredients considered to be non-hazardous rounding to 100%		

SECTION 4: FIRST AID MEASURES

General Advice

If poisoning occurs, contact a doctor or Poisons Information Centre (Australia 13 11 26, New Zealand 0800 764 766).

Inhalation

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek immediate medical advice if effects persist.

Skin Contact

Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye Contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek immediate medical advice.

Notes to Physician

Treat symptomatically. Effects may be delayed.

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 4 of 4

This revision issued October 2020

SECTION 5: FIRE FIGHTING MEASURES

Hazchem Code	3YE
Suitable Extinguishing Media	If material is involved in a fire, use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).
Specific Hazards	Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition, and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated, both in and near the work area. DO NOT SMOKE.
Fire Fighting Further Advice	Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Small Spills	Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.
Large Spills	If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
Dangerous Goods Initial Emergency Response Guide	No. 14

SECTION 7: HANDLING AND STORAGE

Handling	Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or sanding dust.
Storage	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep containers

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 5 of 5

This revision issued October 2020

standing upright. Keep containers closed when not in use. Check regularly for leaks.

This material is a Poison Schedule 5 and must be stored, maintained, and used in accordance with the relevant regulations.

DAINGEROUS GOODS CLASSIFICATION

Dangerous Goods Class	Packing Group	UN Number	Hazchem Code	Poison Schedule (SUSMP)
3	II	1263	3YE	S5

Classified as Dangerous Goods by the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail and the New Zealand NZS5433: Transport of Dangerous Goods on Land

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Chemical Entity	CAS Number	TWA (ppm)	TWA (mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Notices
1-Methoxy-2-propanol acetate	108-65-6	50	274	100	548	SK
Isopropyl alcohol	67-63-0	400	983	500	1230	-
Xylene	1330-20-7	80	350	150	655	-
Ethyl Benzene	100-41-4	100	434	125	543	-
Methyl ethyl ketone (MEK)	78-93-3	150	445	300	890	-

As published by Safe Work Australia.

TWA: The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15-minute period which should not be exceeded at any time during a normal eight-hour workday.

SK Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 6 of 6

This revision issued October 2020

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values

As per the national Model regulations for the control of Workplace Hazardous Substances (Safe Work Australia) the ingredients in this material do not have a Biological Limit Allocated

Engineering Measures

Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment

SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR. Wear safety shoes, overalls, gloves, chemical goggles and respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene Measures

Keep away from food, drink and animal feeding stuffs. When using, do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Form	Liquid
Colour	Black
Odour	Characteristic alcohol
Solubility	Not Available (Partially soluble)
Specific Gravity (20°C)	0.90 – 1.1
Relative Vapour Density (air = 1)	> 1
Vapour Pressure (20°C)	Not Available (M.E.K. 10.5 kPa)
Flash Point (°C)	–10 for M.E.K.
Flammability Limits (%)	Not Available
Auto Ignition Temperature (°C)	Not Available (M.E.K. 404)
Melting Point/Range (°C)	Not Available
Boiling Point/Range (°C)	Not Available (M.E.K. 80°C at 100 kPa)
pH	Not Applicable

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 7 of 7

This revision issued October 2020

Viscosity Not Available
Total VOC (g/Litre) Not Available

(Typical values only. Consult specification sheet)

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability	This material is thermally stable when stored and used as directed.
Conditions to Avoid	Elevated temperatures and sources of ignition.
Incompatible Materials	Incompatible with Oxidising Agents, Natural Rubber, Butyl Rubber, EPDM, Nitrile Rubbers and Polystyrene.
Hazardous Decomposition Products	Oxides of Carbon and Nitrogen, smoke and other toxic fumes.
Hazardous Reactions	No known hazardous reactions.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and over-exposure occurs are:

ACUTE EFFECTS

Inhalation	Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.
Skin Contact	Methyl Ethyl Ketone: LD50 Oral, Rat 2737mg/kg. Contact with skin will result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis. AUH 066 Repeated exposure may cause skin dryness or cracking.
Ingestion	Methyl Ethyl Ketone: LD50 Oral, Rat 2737mg/kg. Toxic if swallowed. Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed.
Eye Contact	An eye irritant. Causes moderate or severe eye irritation

ACUTE TOXICITY

Inhalation	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): 20 mg/L.
Skin Contact	This material has been classified non-hazardous. Acute toxicity estimate (based on ingredients): > 2,000 mg/Kg.

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 8 of 8

This revision issued October 2020

Ingestion	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): > 2,000 mg/Kg
Corrosion/Irritancy	Eye: this material has been classified as a Category 2A hazard (reversible effects to eyes). Skin: this material has been classified as a Category 2 hazard (reversible effects to skin).
Sensitisation	<u>Inhalation:</u> This material has been classified as not a respiratory sensitiser. <u>Skin:</u> This material has been classified as a skin sensitiser Category 1 Hazard.
Aspiration Hazard	This material has been classified as an Aspiration Hazard Category 1A. If large amounts are ingested: Can cause effects as described for inhalation. May be drawn into the lungs if swallowed or vomited, causing severe lung damage. Death can result.
Specific Target Organ Toxicity (single exposure)	This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

CHRONIC TOXICITY

Mutagenicity	This material has been classified as non-hazardous.
Carcinogenicity	This material has been classified as non-hazardous. This product contains up to 5% ethylbenzene. IARC has evaluated ethylbenzene and classified it as a 'possible human carcinogen' Group 2B based on specific evidence for cancer in exposed humans.
Reproductive Toxicity (including via lactation)	This material has been classified as non-hazardous.
Specific Target Organ Toxicity (single exposure)	This material has been classified as non-hazardous, however, we strongly do not recommend contact/use by pregnant or lactating mothers.

SECTION 12: ECOLOGICAL INFORMATION

General Information	Avoid contaminating waterways.
Acute Aquatic Hazard	This material has been classified as a non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L.
Long-Term Aquatic Hazard	This material has been classified as a Category 2 Chronic Hazard. Non-rapidly or rapidly degradable substances for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): > 100 mg/L, where the substance is not rapidly degradable and/or $BCF \leq 500$ and/or $\log Kow \geq 4$
Ecotoxicity	No information available.
Persistence and Degradability	No information available.
Bioaccumulation Potential	No information available.
Mobility	No information available.

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 9 of 9

This revision issued October 2020

SECTION 13: DISPOSAL CONSIDERATIONS

General Information

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see Section 8 of this SDS. If possible, material and its container should be recycled. If material or container cannot be recycled, dispose of in accordance with local, regional, national and international Regulations.

SECTION 14: TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the Australian Code for the Transport of dangerous Goods by Road & Rail and the New Zealand NZS5433: Transport of Dangerous of Goods on Land.

UN No.	1263
Dangerous Goods Class	3
Packing Group	II
Hazchem Code	3YE
Emergency Response Guide No.	14
Proper Shipping Name	PAINTS LFP (MEK, ISOPROPANOL)
Dangerous Goods Diamond	



Segregation Dangerous Goods

Not to be loaded with explosives (Class 1), flammable gasses (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1) infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No.	1263
Dangerous Goods Class	3
Packing Group	II
Hazchem Code	3YE
Emergency Response Guide No.	14
Proper Shipping Name	PAINTS LFP (MEK, ISOPROPANOL)



POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 10 of 10

This revision issued October 2020

Dangerous Goods Diamond



AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No.	1263
Dangerous Goods Class	3
Packing Group	II
Hazchem Code	3YE
Emergency Response Guide No.	14
Proper Shipping Name	PAINTS LFP (MEK, ISOPROPANOL)
Dangerous Goods Diamond	



SECTION 15: REGULATORY INFORMATION

HSNO Group Standard	Surface Coatings and Colourants (Flammable) Group Standard 2006: HSR002662.
This material is not subject to the following international agreements:	Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) International Convention for the Prevention of Pollution from Ships (MARPOL)
This material is subject to the following international agreements:	Basel Convention (Hazardous Waste) Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish
This material/constituent(s) is covered by the following requirements:	The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth). All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

SECTION 16: OTHER INFORMATION

KEY/LEGEND

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th Edition)
AICS	Australian Inventory of Chemical Substances
CAS Number	Chemical Abstracts Service (Registry Number)
CO2	Carbon Dioxide

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)



SAFETY DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

PRODUCT NAME: GalMax™ ETCH Black Etch Primer

Page 11 of 11

This revision issued October 2020

Hazchem Code

Emergency action code of numbers and letters that provide information to emergency services, especially firefighters.

IARC

International Agency for Research on Cancer

KG

Kilograms

LC50

LC stands for Lethal Concentration

LD50

LD stands for Lethal Dose

LT

Litres

N.O.S.

Not Otherwise Specified

NTP

National Toxicology Program (USA)

ppm

Parts per Million

STEL

Short Term Exposure Limit

SUSMP

Standard for the Uniform Scheduling of Medicines & Poisons

SWA

Safe Work Australia, formerly ASCC and NOHSC

TLV

Threshold Limit Value

TWA

Time Weighted Average

UN Number

United Nations Number

This SDS is prepared in accordance with the Safe Work Australia (SWA) document, entitled: **Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice (February 2016).**

This Safety Data Sheet (SDS) summarises our best knowledge of the Health and Safety Hazard information pertaining to this product, including how to safely handle and use the product in the workplace.

Each user must review this SDS in the context of the how the product will be handled and used. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact **Chemtools Pty Ltd**, whereby we will attempt to obtain additional information from our suppliers.

Our responsibility for products sold is subject to our Terms and Conditions, a copy of which is sent to our customers and is also available upon request.

Copyright © Chemtools Pty Ltd



CHEMTOOLS

POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)

SAFETY DATA SHEET BY **CHEMTOOLS PTY LTD** (ABN 12 114 400 083) • HEAD OFFICE/MANUFACTURING FACILITY: UNIT 2, 14 - 16 LEE HOLM ROAD ST MARYS NSW 2760

VISIT US ONLINE: WWW.CHEMTOOLS.COM.AU • PH: 1300 738 250 (AUST) • PH: +61 2 9833 9766 (INT'L) • PROUDLY AUSTRALIAN OWNED & OPERATED