



# Kleanium™ Biodegradable Parts Wash

## Chemtools Pty Ltd

Version No: 4.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **08/04/2024**

Print Date: **08/04/2024**

S.GHS.AUS/NZ.EN.E

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

|                               |                                    |
|-------------------------------|------------------------------------|
| Product name                  | Kleanium™ Biodegradable Parts Wash |
| Chemical Name                 | Not Applicable                     |
| Chemical formula              | Not Applicable                     |
| Other means of identification | Not Available                      |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | Ready to use - degreaser.<br>Use according to manufacturer's directions. |
|--------------------------|--|

#### Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Chemtools Pty Ltd  | Chemtools Ltd  |
|-------------------------|--|--|
| Address                 | Unit 2, 14 - 16 Lee Holm Road St Marys NSW 2760 Australia          | 15/62 Factory Road Belfast Christchurch 8051 New Zealand             |
| Telephone               | 1300 738 250, +61 2 9833 9766                                      | +64 3 323 4177   |
| Fax                     | +61 2 9623 3670  | +61 2 9623 3670  |
| Website                 | <a href="http://www.chemtools.com.au">www.chemtools.com.au</a>     | <a href="http://www.chemtools.co.nz">www.chemtools.co.nz</a>         |
| Email                   | <a href="mailto:sales@chemtools.com.au">sales@chemtools.com.au</a> | <a href="mailto:nzsales@chemtools.co.nz">nzsales@chemtools.co.nz</a> |

#### Emergency telephone number

| Association / Organisation        | Poisons Information Centre | National Poisons Centre |
|-----------------------------------|----------------------------|-------------------------|
| Emergency telephone numbers       | 13 11 26                   | 0800 764 766            |
| Other emergency telephone numbers | Not Available              | Not Available           |

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.**

|                    |  |
|--------------------|--|
| Poisons Schedule   | S5   |
| Classification [1] | Serious Eye Damage/Eye Irritation Category 2A  |
| Legend:            | 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

#### Label elements

|                     |  |
|---------------------|--|
| Hazard pictogram(s) |  |
|---------------------|--|

**Kleanium™ Biodegradable Parts Wash**

**Signal word**     **Warning**

**Hazard statement(s)**

**H319**     Causes serious eye irritation.

**Precautionary statement(s) Prevention**

**P280**     Wear protective gloves, protective clothing, eye protection and face protection.

**P264**     Wash all exposed external body areas thoroughly after handling.

**Precautionary statement(s) Response**

**P305+P351+P338**     IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P337+P313**     If eye irritation persists: Get medical advice/attention.

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

Not Applicable

**Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.**

**NFPA 704 diamond**



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

**Classification** <sup>[1]</sup>     Serious Eye Damage/Eye Irritation Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3

**Legend:**     1. Classification by vendor; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

**Determined by using GHS/HSNO criteria**     6.4A, 9.1C

**Label elements**

**Hazard pictogram(s)**



**Signal word**     **Warning**

**Hazard statement(s)**

**H319**     Causes serious eye irritation.

**H412**     Harmful to aquatic life with long lasting effects.

**Supplementary statement(s)**

Not Applicable

**Precautionary statement(s) Prevention**

**P273**     Avoid release to the environment.

**P280**     Wear protective gloves, protective clothing, eye protection and face protection.

**P264**     Wash all exposed external body areas thoroughly after handling.

**Precautionary statement(s) Response**

**P305+P351+P338**     IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P337+P313**     If eye irritation persists: Get medical advice/attention.

Kleanium™ Biodegradable Parts Wash

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

**P501** Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

**SECTION 3 Composition / information on ingredients**

**Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No        | %[weight] | Name                                       |
|---------------|-----------|--|
| 25155-30-0    | <10       | <u>sodium dodecylbenzenesulfonate</u>      |
| 111-76-2      | <5        | <u>ethylene glycol monobutyl ether</u>     |
| 6834-92-0     | <2        | <u>sodium metasilicate, anhydrous</u>      |
| Not Available | balance   | Ingredients determined not to be hazardous |

**Legend:** 1. Classification by vendor; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

**SECTION 4 First aid measures**

**Description of first aid measures**

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>  |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>       |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul> |

**Indication of any immediate medical attention and special treatment needed**

For acute or short term repeated exposures to ethylene glycol:

- ▶ Early treatment of ingestion is important. Ensure emesis is satisfactory.
- ▶ Test and correct for metabolic acidosis and hypocalcaemia.
- ▶ Apply sustained diuresis when possible with hypertonic mannitol.
- ▶ Evaluate renal status and begin haemodialysis if indicated. [I.L.O]
- ▶ Rapid absorption is an indication that emesis or lavage is effective only in the first few hours. Cathartics and charcoal are generally not effective.
- ▶ Correct acidosis, fluid/electrolyte balance and respiratory depression in the usual manner. Systemic acidosis (below 7.2) can be treated with intravenous sodium bicarbonate solution.
- ▶ Ethanol therapy prolongs the half-life of ethylene glycol and reduces the formation of toxic metabolites.
- ▶ Pyridoxine and thiamine are cofactors for ethylene glycol metabolism and should be given (50 to 100 mg respectively) intramuscularly, four times per day for 2 days.
- ▶ Magnesium is also a cofactor and should be replenished. The status of 4-methylpyrazole, in the treatment regime, is still uncertain. For clearance of the material and its metabolites, haemodialysis is much superior to peritoneal dialysis.

[Ellenhorn and Barceloux: Medical Toxicology]

It has been suggested that there is a need for establishing a new biological exposure limit before a workshift that is clearly below 100 mmol ethoxy-acetic acids per mole creatinine in morning urine of people occupationally exposed to ethylene glycol ethers. This arises from the finding that an increase in urinary stones may be associated with such exposures.

Continued...

Laitinen J., et al: Occupational & Environmental Medicine 1996; 53, 595-600

## SECTION 5 Firefighting measures

### Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

|                              |   |
|------------------------------|---|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Non combustible.</li> <li>▶ Not considered to be a significant fire risk.</li> <li>▶ Expansion or decomposition on heating may lead to violent rupture of containers.</li> <li>▶ Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> </ul> <p>Decomposition may produce toxic fumes of:<br/>carbon dioxide (CO<sub>2</sub>)<br/>sulfur oxides (SO<sub>x</sub>)<br/>other pyrolysis products typical of burning organic material.<br/>May emit poisonous fumes.<br/>May emit corrosive fumes.</p>  |

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>   |
| <b>Major Spills</b> | <p>Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                      |   |
|----------------------|---|
| <b>Safe handling</b> | ▶ <b>DO NOT</b> allow clothing wet with material to stay in contact with skin |
|----------------------|---|

Continued...

**Kleanium™ Biodegradable Parts Wash**

|                          |   |
|--------------------------|---|
|                          | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Avoid contact with moisture.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>   |

**Conditions for safe storage, including any incompatibilities**

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Polyethylene or polypropylene container.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul>  |



X — Must not be stored together  
O — May be stored together with specific preventions  
+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

**SECTION 8 Exposure controls / personal protection**

**Control parameters**

**Occupational Exposure Limits (OEL)**

**INGREDIENT DATA**

| Source   | Ingredient                      | Material name                        | TWA                 | STEL               | Peak          | Notes                    |
|--|---------------------------------|--------------------------------------|---------------------|--------------------|---------------|--------------------------|
| Australia Exposure Standards                   | ethylene glycol monobutyl ether | 2-Butoxyethanol                      | 20 ppm / 96.9 mg/m3 | 242 mg/m3 / 50 ppm | Not Available | Not Available            |
| New Zealand Workplace Exposure Standards (WES) | ethylene glycol monobutyl ether | 2-Butoxyethanol (Butyl glycol ether) | 25 ppm / 121 mg/m3  | Not Available      | Not Available | (skin) - Skin absorption |

**Emergency Limits**

| Ingredient                      | TEEL-1    | TEEL-2   | TEEL-3    |
|---------------------------------|-----------|----------|-----------|
| sodium dodecylbenzenesulfonate  | 2.1 mg/m3 | 23 mg/m3 | 87 mg/m3  |
| ethylene glycol monobutyl ether | 60 ppm    | 120 ppm  | 700 ppm   |
| sodium metasilicate, anhydrous  | 3.8 mg/m3 | 42 mg/m3 | 250 mg/m3 |


| Ingredient                      | Original IDLH | Revised IDLH  |
|---------------------------------|---------------|---------------|
| sodium dodecylbenzenesulfonate  | Not Available | Not Available |
| ethylene glycol monobutyl ether | 700 ppm       | Not Available |
| sodium metasilicate, anhydrous  | Not Available | Not Available |

**Kleanium™ Biodegradable Parts Wash**

**Occupational Exposure Banding**

| Ingredient                     | Occupational Exposure Band Rating   | Occupational Exposure Band Limit |
|--------------------------------|---|----------------------------------|
| sodium dodecylbenzenesulfonate | E   | ≤ 0.01 mg/m <sup>3</sup>         |
| sodium metasilicate, anhydrous | E   | ≤ 0.01 mg/m <sup>3</sup>         |
| <b>Notes:</b>                  | <i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i> |                                  |

**Exposure controls**

| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.</p> <p>An approved self contained breathing apparatus (SCBA) may be required in some situations.</p> <p>Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|---|---|----------------------|------------|--|------------------------------|---|----------------------------|--|----------------------------|--|------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
| Type of Contaminant:  | Air Speed:  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min.)  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5-10 m/s (500-2000 f/min.)  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Lower end of the range  | Upper end of the range  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Individual protection measures, such as personal protective equipment</b>  |    |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Eye and face protection</b>  | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Skin protection</b>  | See Hand protection below   |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Hands/feet protection</b>  | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul>  |                      |            |  |                              |   |                            |  |                            |  |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |

**Kleanium™ Biodegradable Parts Wash**

**NOTE:**

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

**Body protection** See Other protection below

- Other protection**
- ▶ Overalls.
  - ▶ P.V.C apron.
  - ▶ Barrier cream.
  - ▶ Skin cleansing cream.
  - ▶ Eye wash unit.

**Ansell Glove Selection**

| Glove — In order of recommendation |
|------------------------------------|
| AlphaTec® 15-554                   |
| AlphaTec® Solvex® 37-185           |
| AlphaTec® 38-612                   |
| AlphaTec® 58-008                   |
| AlphaTec® 58-735                   |
| AlphaTec® Solvex® 37-675           |
| AlphaTec® 58-530W                  |
| AlphaTec® 79-700                   |
| DermaShield™ 73-711                |
| MICROFLEX® 93-244                  |

The suggested gloves for use should be confirmed with the glove supplier.

**Respiratory protection**

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator  |
|------------------------------------|----------------------|----------------------|-------------------------|
| up to 10 x ES                      | A-AUS P2             | -                    | A-PAPR-AUS / Class 1 P2 |
| up to 50 x ES                      | -                    | A-AUS / Class 1 P2   | -                       |
| up to 100 x ES                     | -                    | A-2 P2               | A-PAPR-2 P2 ^           |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## Kleanium™ Biodegradable Parts Wash

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                   | Green / purple non-viscous liquid with a characteristic odour; mixes with water. Coloured |  |                |
| <b>Physical state</b>                               | Liquid  | <b>Relative density (Water = 1)</b>            | 1.01-1.03      |
| <b>Odour</b>  | Characteristic  | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Applicable |
| <b>pH (as supplied)</b>                             | 11.5-12.0   | <b>Decomposition temperature (°C)</b>          | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | 0 approx.   | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | 100 approx.   | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Applicable  | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available   | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Applicable  | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Applicable  | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Applicable  | <b>Volatile Component (%vol)</b>               | 85 ca.         |
| <b>Vapour pressure (kPa)</b>                        | Not Available   | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water</b>                          | Miscible  | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available   | <b>VOC g/L</b>                                 | 0              |

## SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

## Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | Not normally a hazard due to non-volatile nature of product<br>Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.  |
| <b>Ingestion</b>    | Accidental ingestion of the material may be damaging to the health of the individual.<br>Ingestion of anionic surfactants may produce diarrhoea, bloated stomach, and occasional vomiting.   |
| <b>Skin Contact</b> | Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br>Anionic surfactants can cause skin redness and pain, as well as a rash. Cracking, scaling and blistering can occur. |
| <b>Eye</b>          | This material can cause eye irritation and damage in some persons.<br>Direct eye contact with some anionic surfactants in high concentration can cause severe damage to the cornea. Low concentrations can cause discomfort, excess blood flow, and corneal clouding and swelling. Recovery may take several days.   |
| <b>Chronic</b>      | Prolonged or repeated skin contact may cause degreasing, followed by drying, cracking and skin inflammation.<br>Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures.<br>Exposure to sulfonates can cause an imbalance in cellular salts and therefore cellular function. Airborne sulfonates may be responsible for respiratory allergies and, in some instances, minor dermal allergies.   |

Continued...



Kleanium™ Biodegradable Parts Wash

| Kleanium™ Biodegradable Parts Wash | TOXICITY  | IRRITATION   |
|------------------------------------|---|--|
|                                    | Not Available   | Not Available  |
| sodium dodecylbenzenesulfonate     | TOXICITY  | IRRITATION   |
|                                    | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>   | Eye (rabbit): 0.25 mg/24hr-SEVERE                                |
|                                    | Inhalation (Rat) LC50: 0.31 mg/L4h <sup>[1]</sup>   | Eye (rabbit): 1% - SEVERE  |
|                                    | Oral (Rat) LD50: 438 mg/kg <sup>[2]</sup>   | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|                                    |   | Skin (rabbit): 20 mg/24 hr-SEVERE                                |
|                                    |   | Skin: adverse effect observed (corrosive) <sup>[1]</sup>         |
|                                    |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| ethylene glycol monobutyl ether    | TOXICITY  | IRRITATION   |
|                                    | dermal (guinea pig) LD50: 210 mg/kg <sup>[2]</sup>  | Eye (rabbit): 100 mg SEVERE * [Union Carbide]                    |
|                                    | Inhalation (Rat) LC50: 450 ppm4h <sup>[2]</sup>   | Eye (rabbit): 100 mg/24h-moderate                                |
|                                    | Oral (Rat) LD50: 250 mg/kg <sup>[2]</sup>   | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|                                    |   | Skin (rabbit): 500 mg, open; mild                                |
|                                    |   | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
|                                    |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| sodium metasilicate, anhydrous     | TOXICITY  | IRRITATION   |
|                                    | dermal (rat) LD50: >5000 mg/kg <sup>[1]</sup>   | Skin (human): 250 mg/24h SEVERE                                  |
|                                    | Inhalation (Rat) LC50: >2.06 mg/l4h <sup>[1]</sup>  | Skin (rabbit): 250 mg/24h SEVERE                                 |
|                                    | Oral (Rat) LD50: 1153 mg/kg <sup>[2]</sup>  |  |
| <b>Legend:</b>                     | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |  |

|  |  |
|--|--|
| <b>SODIUM DODECYLBENZENESULFONATE</b>  | Linear alkyl benzene sulfonates are derived from strong corrosive acids. Animal testing has shown they can cause skin reactions, eye irritation, sluggishness, passage of frequent watery stools, weakness and may lead to death. They may also react with surfaces of the mouth and intestines, depending on the concentration exposed to. There is no evidence of harm to the unborn baby or tendency to cause cancer.   |
| <b>ETHYLENE GLYCOL MONOBUTYL ETHER</b> | <p>NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high concentrations of this substance by all routes. ** ASCC (NZ) SDS</p> <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>For ethylene glycol monoalkyl ethers and their acetates (EGMAEs):</p> <p>Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE) and their acetates.</p> <p>EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol ethers.</p> <p><b>Acute Toxicity:</b> Oral LD50 values in rats for all category members range from 739 (EGHE) to 3089 mg/kg bw (EGPE), with values increasing with decreasing molecular weight. Four to six hour acute inhalation toxicity studies were conducted for these chemicals in rats at the highest vapour concentrations practically achievable. Values range from LC0 &gt; 85 ppm (508 mg/m3) for EGHE, LC50 &gt; 400ppm (2620 mg/m3) for EGBEA to LC50 &gt; 2132 ppm (9061 mg/m3) for EGPE. No lethality was observed for any of these materials under these conditions. Dermal LD50 values in rabbits range from 435 mg/kg bw (EGBE) to 1500 mg/kg bw (EGBEA). Overall these category members can be considered to be of low to moderate acute toxicity. All category members cause reversible irritation to skin and eyes, with EGBEA less irritating and EGHE more irritating than the other category members. EGPE and EGBE are not sensitizers in experimental animals or humans. Signs of acute toxicity in rats, mice and rabbits are consistent with haemolysis (with the exception of EGHE) and non-specific CNS depression typical of organic solvents in general. Alkoxyacetic acid metabolites, propoxyacetic acid (PAA) and butoxyacetic acid (BAA), are responsible for the red blood cell hemolysis. Signs of toxicity in humans deliberately ingesting cleaning fluids containing 9-22% EGBE are similar to those of rats, with the exception of haemolysis. Although decreased blood haemoglobin and/or haemoglobinuria were observed in some of the human cases, it is not clear if this was due to haemolysis or haemodilution as a result of administration of large volumes of fluid. Red blood cells of humans are many-fold more resistant to toxicity from EGPE and EGBE <i>in vitro</i> than those of rats.</p> <p><b>Repeat dose toxicity:</b> The fact that the NOAEL for repeated dose toxicity of EGBE is less than that of EGPE is consistent with red blood cells being more sensitive to EGBE than EGPE. Blood from mice, rats, hamsters, rabbits and baboons were sensitive to the effects of BAA <i>in vitro</i> and displayed similar responses, which included erythrocyte swelling (increased haematocrit and mean corpuscular hemoglobin), followed by hemolysis. Blood from humans, pigs, dogs, cats, and guinea pigs was less sensitive to haemolysis by BAA <i>in vitro</i>.</p> |

**Kleanium™ Biodegradable Parts Wash**

|   |  |
|---|--|
|   | <p><b>Mutagenicity:</b> In the absence and presence of metabolic activation, EGBE tested negative for mutagenicity in Ames tests conducted in <i>S. typhimurium</i> strains TA97, TA98, TA100, TA1535 and TA1537 and EGHE tested negative in strains TA98, TA100, TA1535, TA1537 and TA1538. <i>In vitro</i> cytogenicity and sister chromatid exchange assays with EGBE and EGHE in Chinese Hamster Ovary Cells with and without metabolic activation and <i>in vivo</i> micronucleus tests with EGBE in rats and mice were negative, indicating that these glycol ethers are not genotoxic.</p> <p><b>Carcinogenicity:</b> In a 2-year inhalation chronic toxicity and carcinogenicity study with EGBE in rats and mice a significant increase in the incidence of liver haemangiosarcomas was seen in male mice and forestomach tumours in female mice. It was decided that based on the mode of action data available, there was no significant hazard for human carcinogenicity.</p> <p><b>Reproductive and developmental toxicity.</b> The results of reproductive and developmental toxicity studies indicate that the glycol ethers in this category are not selectively toxic to the reproductive system or developing fetus, developmental toxicity is secondary to maternal toxicity. The repeated dose toxicity studies in which reproductive organs were examined indicate that the members of this category are not associated with toxicity to reproductive organs (including the testes). Results of the developmental toxicity studies conducted via inhalation exposures during gestation periods on EGPE (rabbits -125, 250, 500 ppm or 531, 1062, or 2125 mg/m<sup>3</sup> and rats - 100, 200, 300, 400 ppm or 425, 850, 1275, or 1700 mg/m<sup>3</sup>), EGBE (rat and rabbit - 25, 50, 100, 200 ppm or 121, 241, 483, or 966 mg/m<sup>3</sup>), and EGHE (rat and rabbit - 20.8, 41.4, 79.2 ppm or 124, 248, or 474 mg/m<sup>3</sup>) indicate that the members of the category are not teratogenic. The NOAELs for developmental toxicity are greater than 500 ppm or 2125 mg/m<sup>3</sup> (rabbit-EGPE), 100 ppm or 425 mg/m<sup>3</sup> (rat-EGPE), 50 ppm or 241 mg/m<sup>3</sup> (rat EGBE) and 100 ppm or 483 mg/m<sup>3</sup> (rabbit EGBE) and greater than 79.2 ppm or 474 mg/m<sup>3</sup> (rat and rabbit-EGHE).</p> <p>Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both the mother and the embryo. Reproductive effects were thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thought that in animals butoxyethanol may cause generalized clotting and bone infarction. In animals, 2-butoxyethanol also increased the rate of some cancers, including liver cancer.</p> |
| <p><b>SODIUM METASILICATE, ANHYDROUS</b></p>                                      | <p>The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.</p>   |
| <p><b>SODIUM DODECYLBENZENESULFONATE &amp; SODIUM METASILICATE, ANHYDROUS</b></p> | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p>   |

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✗ | Carcinogenicity          | ✗ |
| Skin Irritation/Corrosion         | ✗ | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation     | ✗ | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity                      | ✗ | Aspiration Hazard        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

**SECTION 12 Ecological information**

**Toxicity**

| Kleanium™ Biodegradable Parts Wash | Endpoint      | Test Duration (hr) | Species                       | Value           | Source        |
|------------------------------------|---------------|--------------------|-------------------------------|-----------------|---------------|
|                                    | Not Available | Not Available      | Not Available                 | Not Available   | Not Available |
| sodium dodecylbenzenesulfonate     | Endpoint      | Test Duration (hr) | Species                       | Value           | Source        |
|                                    | EC50          | 48h                | Crustacea                     | 0.065-0.085mg/L | 4             |
|                                    | EC50          | 96h                | Algae or other aquatic plants | 0.9mg/L         | 5             |
|                                    | EC50          | 72h                | Algae or other aquatic plants | 21mg/l          | 2             |
|                                    | LC50          | 96h                | Fish                          | 0.59mg/L        | 4             |
|                                    | EC50(ECx)     | 48h                | Crustacea                     | 0.065-0.085mg/L | 4             |
| ethylene glycol monobutyl ether    | Endpoint      | Test Duration (hr) | Species                       | Value           | Source        |
|                                    | EC50          | 96h                | Algae or other aquatic plants | 720mg/l         | 2             |
|                                    | EC50          | 48h                | Crustacea                     | 164mg/l         | 2             |

Continued...

**Kleanium™ Biodegradable Parts Wash**

|  |           |     |                               |          |               |
|--|-----------|-----|-------------------------------|----------|---------------|
|  | EC50      | 72h | Algae or other aquatic plants | 623mg/l  | 2             |
|  | EC10(ECx) | 48h | Crustacea                     | 7.2mg/l  | 2             |
|  | LC50      | 96h | Fish                          | 1700mg/l | Not Available |

| sodium metasilicate, anhydrous | Endpoint  | Test Duration (hr) | Species                       | Value           | Source |
|--------------------------------|-----------|--------------------|-------------------------------|-----------------|--------|
|                                | EC50(ECx) | 48h                | Crustacea                     | 22.94-49.01mg/l | 4      |
|                                | EC50      | 72h                | Algae or other aquatic plants | 207mg/l         | 2      |
|                                | LC50      | 96h                | Fish                          | 180mg/l         | 1      |
|                                | EC50      | 48h                | Crustacea                     | 22.94-49.01mg/l | 4      |

**Legend:** Extracted from 1. IUCLED Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

| Ingredient                      | Persistence: Water/Soil   | Persistence: Air            |
|---------------------------------|---------------------------|-----------------------------|
| ethylene glycol monobutyl ether | LOW (Half-life = 56 days) | LOW (Half-life = 1.37 days) |

**Bioaccumulative potential**

| Ingredient                      | Bioaccumulation  |
|---------------------------------|------------------|
| ethylene glycol monobutyl ether | LOW (BCF = 2.51) |

**Mobility in soil**

| Ingredient                      | Mobility           |
|---------------------------------|--------------------|
| ethylene glycol monobutyl ether | HIGH (Log KOC = 1) |

**SECTION 13 Disposal considerations**

**Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|-------------------------------------|--|

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

**Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

**Kleanium™ Biodegradable Parts Wash**

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

**SECTION 14 Transport information**

**Labels Required**

|                         |                |
|-------------------------|----------------|
| <b>Marine Pollutant</b> | NO             |
| <b>HAZCHEM</b>          | Not Applicable |

**Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name                    | Group         |
|---------------------------------|---------------|
| sodium dodecylbenzenesulfonate  | Not Available |
| ethylene glycol monobutyl ether | Not Available |
| sodium metasilicate, anhydrous  | Not Available |

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name                    | Ship Type     |
|---------------------------------|---------------|
| sodium dodecylbenzenesulfonate  | Not Available |
| ethylene glycol monobutyl ether | Not Available |
| sodium metasilicate, anhydrous  | Not Available |

**SECTION 15 Regulatory information**

**Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard   |
|------------|--|
| HSR002521  | Animal Nutritional and Animal Care Products Group Standard 2020                                      |
| HSR002530  | Cleaning Products Subsidiary Hazard Group Standard 2020  |
| HSR002535  | Gases under Pressure Mixtures Subsidiary Hazard Group Standard 2020                                  |
| HSR002503  | Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020                  |
| HSR002606  | Lubricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020 |
| HSR002612  | Metal Industry Products Subsidiary Hazard Group Standard 2020  |
| HSR002624  | N.O.S. Subsidiary Hazard Group Standard 2020   |
| HSR002638  | Photographic Chemicals Subsidiary Hazard Group Standard 2020   |
| HSR002644  | Polymers Subsidiary Hazard Group Standard 2020   |
| HSR002647  | Reagent Kits Group Standard 2020   |
| HSR002648  | Refining Catalysts Group Standard 2020   |
| HSR002653  | Solvents Subsidiary Hazard Group Standard 2020   |
| HSR002670  | Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020                                |
| HSR002684  | Water Treatment Chemicals Subsidiary Hazard Group Standard 2020                                      |

**Kleanium™ Biodegradable Parts Wash**

| HSR Number | Group Standard  |
|------------|---|
| HSR100425  | Pharmaceutical Active Ingredients Group Standard 2020                                       |
| HSR002600  | Leather and Textile Products Subsidiary Hazard Group Standard 2020                          |
| HSR002544  | Construction Products Subsidiary Hazard Group Standard 2020                                 |
| HSR002549  | Corrosion Inhibitors Subsidiary Hazard Group Standard 2020                                  |
| HSR002552  | Cosmetic Products Group Standard 2020   |
| HSR002558  | Dental Products Subsidiary Hazard Group Standard 2020                                       |
| HSR002565  | Embalming Products Subsidiary Hazard Group Standard 2020                                    |
| HSR002571  | Fertilisers Subsidiary Hazard Group Standard 2020   |
| HSR002573  | Fire Fighting Chemicals Group Standard 2021   |
| HSR002578  | Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020                |
| HSR002585  | Fuel Additives Subsidiary Hazard Group Standard 2020  |
| HSR002596  | Laboratory Chemicals and Reagent Kits Group Standard 2020                                   |
| HSR100580  | Tattoo and Permanent Makeup Substances Group Standard 2020                                  |
| HSR100757  | Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020                    |
| HSR100758  | Veterinary Medicines Non dispersive Closed System Application Group Standard 2020           |
| HSR100759  | Veterinary Medicines Non dispersive Open System Application Group Standard 2020             |
| HSR100592  | Agricultural Compounds Special Circumstances Group Standard 2020                            |
| HSR100756  | Active Ingredients for Use in the Manufacture of Agricultural Compounds Group Standard 2020 |

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

**sodium dodecylbenzenesulfonate is found on the following regulatory lists**

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
- Australian Inventory of Industrial Chemicals (AIIC)
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
- New Zealand Inventory of Chemicals (NZIoC)
- New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

**ethylene glycol monobutyl ether is found on the following regulatory lists**

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
- Australian Inventory of Industrial Chemicals (AIIC)
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
- New Zealand Approved Hazardous Substances with controls
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
- New Zealand Inventory of Chemicals (NZIoC)
- New Zealand Workplace Exposure Standards (WES)

**sodium metasilicate, anhydrous is found on the following regulatory lists**

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australian Inventory of Industrial Chemicals (AIIC)
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
- New Zealand Inventory of Chemicals (NZIoC)

**Additional Regulatory Information**

Not Applicable

**Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class   | Quantities     |
|----------------|----------------|
| Not Applicable | Not Applicable |

**Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Kleanium™ Biodegradable Parts Wash

| Class of substance | Quantities     |
|--------------------|----------------|
| Not Applicable     | Not Applicable |

Refer Group Standards for further information

**Maximum quantities of certain hazardous substances permitted on passenger service vehicles**

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class   | Gas (aggregate water capacity in mL) | Liquid (L)     | Solid (kg)     | Maximum quantity per package for each classification |
|----------------|--------------------------------------|----------------|----------------|--|
| Not Applicable | Not Applicable                       | Not Applicable | Not Applicable | Not Applicable                                       |

**Tracking Requirements**

Not Applicable

**National Inventory Status**

| National Inventory                             | Status   |
|--|--|
| Australia - AIC / Australia Non-Industrial Use | Yes  |
| Canada - DSL                                   | Yes  |
| Canada - NDSL                                  | No (sodium dodecylbenzenesulfonate; ethylene glycol monobutyl ether; sodium metasilicate, anhydrous)   |
| China - IECSC                                  | Yes  |
| Europe - EINEC / ELINCS / NLP                  | Yes  |
| Japan - ENCS                                   | Yes  |
| Korea - KECI                                   | Yes  |
| New Zealand - NZIoC                            | Yes  |
| Philippines - PICCS                            | Yes  |
| USA - TSCA                                     | Yes  |
| Taiwan - TCSI                                  | Yes  |
| Mexico - INSQ                                  | Yes  |
| Vietnam - NCI                                  | Yes  |
| Russia - FBEPH                                 | Yes  |
| <b>Legend:</b>                                 | <p>Yes = All CAS declared ingredients are on the inventory</p> <p>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</p> |

**SECTION 16 Other information**

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 08/04/2024 |
| <b>Initial Date</b>  | 27/03/2024 |

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.