



TECHNICAL DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

Issued: February 2022

Rapidstick™ Multi-Surface Adhesive Spray

PART NUMBER	AVAILABLE SIZE
8-ADS-400 (Prev CT-R25-400 & 8-4125-400)	400g Aerosol

PRODUCT DESCRIPTION

Chemtools® Rapidstick™ Multi-Surface Adhesive Spray is an advanced and versatile rubber tack for adhering a variety of materials in applications ranging from light to heavy duty. It provides speedy bonding after a conveniently long open time to allow for the repositioning and adjustment of surfaces.

Rapidstick™ Adhesive Spray is expelled as a mist from a moderate flow-rate spray valve to provide over-spray control. It is ideal for industrial repair and improvements, framing, crafts, and other projects, and is suitable for affixing most metals, felt, cork, fabrics, plastics, paper, corrugated cardboard, wood, and a variety of other materials.

DIRECTIONS (READ LABEL BEFORE USE)

Ensure bonding surfaces are clean, dry, and free of greases and other contaminants.

Shake can before use, then spray evenly over one surface, or both surfaces for a stronger bond.

Wait 3 minutes after spraying to allow the adhesive time to become tacky, and then press surfaces together and allow to dry. If surfaces are prone to separation, hold or clamp in position until dry.

While the adhesive spray will provide an initial bond, full bond strength will be achieved after 24 hrs.

Note: Unsuitable for use on solvent sensitive plastics and polystyrene.

TECHNICAL DATA

Colour:	Off-White to Pale yellow
Odour:	Solvent
Active Solids:	17%
Adhesive Type:	Synthetic Rubber
VOC Content:	491g/L
Propellant:	Hydrocarbon



TECHNICAL DATA SHEET

A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

FIRST AID & SAFETY PRECAUTIONS

Please refer to Safety Data Sheet (SDS) before use. Use with adequate ventilation and avoid breathing fumes. Avoid contact with eyes and skin. This product may produce adverse health conditions, ranging from minor skin irritation to serious systemic effects. It should not be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheet (SDS) for this product have been fully understood by all persons who will work with the material.

STORAGE

Keep out of reach of children. Store below 30°C. Protect from direct sunlight. Do not expose to temperatures exceeding 50°C.

Containers must be secured and stored upright during transit.

DISCLAIMER

Chemtools® has made every effort to ensure the information provided in this Technical Data Sheet is accurate at the time of publication. Chemtools® expressly recommends that the user make his/her own assessment to determine the suitability of the product for its intended purpose prior to application. Chemtools shall not be responsible for loss, damage, or injury, resulting from the reliance upon, or failure to adhere to, any recommendations or information contained herein; nor from abnormal use of the material; nor from any hazard inherent in the nature of the material.

FURTHER INFORMATION

Please visit Chemtools® online at www.chemtools.com.au for product photos, marketing materials, Technical Data Sheets, Safety Data Sheets, contact details, and other company/business related information.