

Rapidstick™

STICK IT LIKE YOU MEAN IT

NO SLUMP • SINGLE COMPONENT • NEUTRAL CURE

UV RESISTANT • WILL NOT FADE, SHRINK, CRACK, OR PEEL



COMPATIBILITY

- ✓ PRIMED & UN-PRIMED
- ✓ COMMERCIAL PAINTS, COATINGS & GLAZES
- ✓ ELECTRONIC PRINTED CIRCUIT BOARDS & COMPONENTS
- ✓ ELECTRICAL DEVICES
- ✓ EXPANSION JOINTS
- ✓ TIMBER & WOOD
- ✓ CONCRETE & BRICKS
- ✓ MOST PLASTICS
- ✓ ALL METALS, INCL. SOFT & COATED
- ✓ MIRRORS & GLASS
- ✓ LAMINATES
- ✓ DRYWALL & PLASTER
- ✓ GRANITE, PORCELAIN, MARBLE & STONE
- ✓ CERAMICS

... AND MANY OTHERS

TECHNICAL DATA

SPECIFIC GRAVITY:	1.4 - 1.6
TACK TIME:	20 MINS
SKIN TIME:	10 MINS
ELONGATION:	213%
APPLICATION:	+15°C TO +40°C
SERVICE TEMP:	-40°C TO +90°C

DURABLE, NON-TACKY,
NON-TOXIC &
HIGHLY ADHESIVE

WILL NOT DEGRADE
OR LOSE
FLEXIBILITY WITH
TIME

FORMULATED FOR
HARSH
ENVIRONMENTS
& EXTREME
TEMPERATURES

LOW ODOUR • MOULD/MILDEW RESISTANT • LIFETIME PERFORMANCE

AVAILABLE COLOURS

- SILVER P/N: 8-RS60SV-300
- WHITE P/N: 8-RS60WT-300

- GREY P/N: 8-RS60GY-300
- BLACK P/N: 8-RS60BK-300
- CLEAR P/N: 8-RS60CL-300

TO PLACE AN ORDER
SEE ATTACHED FORM